

BGP GREEN 70/90

Per escavatori 1.5-4.0 ton / For excavators 1.5-4.0 ton

TRINCIATRICI IDRAULICHE
HYDRAULIC MULCHERS



BGP GREEN 70

BGP GREEN 90




HF2

Ø max 5 cm










KC1

Ø max 3 cm



Via Giuseppe Antonucci 3
06012 - Città di Castello (Perugia - Italy)
Tel: +39 (0)75 8556347 - Fax: +39 (0)75 8524266
E-mail: info@officinecmeccanicabeg.com
www.officinecmeccanicabeg.com



Modelo	 (ton)	 (cm / ft)	 (LxAxH cm) (LxWxH ft)	PESO kg weight lb	Cilindrada motor	 (L/min) (gal/min)	 bar (min-max)	Transmisión	Rotor	
BGP GREEN 70	1.5-4.0	70 cm 2.29 ft	95x55x45 3.11x1.80x1.47	130 kg 287 lb	8-11-16	20-30-40 5.28-7.92-10.56	170-220	directa	helicoidal	10
BGP GREEN 90	2.0-4.0	90 cm 2.95 ft	115x55x45 3.77x1.80x1.47	150 kg 331 lb	11-16	30-40 7.92-10.56	170-220	directa	helicoidal	14

CARATTERISTICHE TECNICHE E DOTAZIONI STANDARD

- Trasmissione diretta.
- Cofanatura interna a doppia cassa con intercapedine.
- Rullo di appoggio regolabile su 3 posizioni per variare l'altezza di taglio.
- Rotore elicoidale con mazze bonificate o coltelli intercambiabili.
- Protezione carter motore.
- Supporti rotore interni con labirinto per la protezione dei cuscinetti dalle impurità.
- Cuscinetti rotore a doppia corona di sfere orientabili di prima qualità.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anti-cavitazione.
- Motore ad ingranaggi.
- Protezioni antinfortunistiche in gomma a norma CE.

TECHNICAL FEATURES AND STANDARD EQUIPMENT

- Direct transmission.
- Internally reinforced with double metal sheet.
- Feeler roller adjustable on 3 positions to change the height of the cut.
- Helicoidal rotor with austempered hammers or blade interchangeable.
- Protective cover for motor.
- Inside rotor supports with labyrinth for the protection of the bearings from the impurities.
- Double row spherical adjustable bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Gear motor.
- Accident prevention rubber protections according to EC directives.

ACCESSORI


- 1 - Attacco sella a perni.
- 2 - Kit tubi Lg. 2 metri.
- 3 - Protezione a catene anteriore.
- 4 - Supporto autolivellante (+30kg).

ACCESSORIES

- 1 - Mounting hitch & pins.
- 2 - Hoses kit Lg. 2 meters.
- 3 - Front chain protection.
- 4 - Self-levelling support (+30kg).



1



3



4